



Optional Extras Interroll Drum Motor 216i/ Idler Pulley 216i

Specifications	Drum Motor type 216i 3-phase	Idler Pulley 216i
Shaft		
Mild steel	Std.	Std.
Stainless steel TS	X	X
Screw hole M10 in shaft (for using with mounting brackets)	X	X
Shell		
Mild steel crowned	Std.	Std.
Stainless steel TS crowned	X	X
Mild steel or stainless steel cylindrical	X	X
Black rubber lagging	o	X
White or blue food quality lagging oil and fat resistant	o	o
Profiled rubber lagging for modular belting	o	o
Sprockets for modular belting	o	o
V-grooves in the rubber lagging	o	o
Special crowns and grooves in shell	o	o
Electrical motors		
Asynchronous 3-phase (DIN IEC 34)	Std.	
Voltage 3x 230/400 with +/-10% tolerance, 50 Hz – IEC 38	Std.	
Special voltages	X	
Insulation class F	Std.	
De-rated motor for modular or no belt application	o	
Dual voltage connection (star/delta) 230/400 V 50 Hz	Std.	
UL/cUL recognised motors	X	
Oil cooled	Std.	
Thermal protector	Std.	
Food grade oil & grease (FDA and USDA)	X	
Electrical connection		
IP 66/67 aluminium terminal box	Std.	
IP 66/67 powder coated food approved terminal box	X	
IP 66/67 stainless steel terminal box	X	
IP 66/67 with straight or elbow connector	X	
IP 66/67 with straight or elbow connector stainless steel	X	
Screened cable (for brakes, encoders and frequency converters)	X	
Halogen-free cable	X	
Other options		
Electromagnetic brake (Minimum RL dimensions increases by 50 mm)	X	
Mechanical backstop	X	
Modified for vertical or angled mounting	X	
Operation with VFD	Std.	
Integrated encoder (Minimum RL dimensions increases by 50 mm)	X	
Degree of protection IP 66/67	Std.	Std.

Note!
Combined brake and encoder not possible.

X = Optional extras
Std. = Fitted as standard
o = Available as option with some limitations
Please consult Interroll